

VANDAL PROOF DOME CAMERA

KVC-612F, KVC-624F

3-AXIS, WDR, VANDAL PROOF DOME CAMERA



IP66



- FEATURES -

- 1/3" Dramatically dynamic range sensor
- High Resolution (up to 550TVL Equivalent)
- Super WDR : Wide Dynamic Range
- True Day & Night : Filter Switching Mechanism Built-in
- Digital Day & Night, 6 Privacy Masking Zones
- Built-in OSD (On Screen Display) Menu
- IP-66 Weatherproof system

* **KVC-612F** : DC 12V Only

* **KVC-624F** : AC 24V / DC 12V (Dual Voltage)

Option

- Varifocal Lens : 4.0~9.0mm DC / 2.8~11.0mm DC



Color



Day & Night



Filter Switching Mechanism



Wide Dynamic Range



DSS Function 0.08Lux



VANDAL PROOF



3-Axis Gimbal



IP-66



Varifocal LENS





12V DC




24V AC / 12V DC Dual Voltage

- DIMENSION -



- 3 AXIS GIMBAL BRACKET -



- Camera Rotation : 360°
- Tilt Rotation : 100°
- Pan Rotation : 270°

- WALL MOUNT BRACKET -



MBR-401WM

- SPECIFICATION -

KVC-612F / KVC-624F		
Signal Format	NTSC	PAL
Horizontal Resolution	550TV lines	
Image Sensor	1/3" Dramatically dynamic range sensor	
Scanning Frequency	15.734KHz(H), 59.94(V)	15.625KHz(H), 50.00(V)
Synchronization	Internal	
Video Output	Standard composite 1Vp-p composite video into 75Ω	
Min. Illumination	Color : 0.4Lux/F1.2, Sense-up x32 : 0.08Lux/F1.2	
Electronic Shutter	1/60 ~ 1/100,000 sec Auto	1/50 ~ 1/100,000 sec Auto
Signal to Noise Ratio	More than 50dB	
True Day & Night	Filter Switching Mechanism Built-in	
White Balance	Auto / ATW DESAT / AWC / Manual	
DSS	OFF / 2 Fields ~ 32 Fields	
DNR	ON / OFF	
Flip	OFF / H.FLIP / V.FLIP / H-H.FLIP	
AGC	LOW / MIDDLE / HIGH	
Camera ID	ON / OFF	
Wide Dynamic Range	Max 120dB / 17-bit	
Privacy Zones	OFF / ON (White, Black, Red)	
Input Voltage	DC 12V (8V - 18V), AC 24V (20V-30V)	
Operating Temperature	-10°C to +55°C	
Storage Temperature	-20°C to +70°C	
Operating Humidity	Under 90% Non-condensing	
Storage Humidity	Under 90% Non-condensing	
Dimension	141.4(Φ) x 106.5(H)mm	
Weight	770g	