

VANDAL PROOF DOME CAMERA

SVC-3242HQ

3-AXIS, VANDAL PROOF DOME CAMERA



- FEATURES -

- 1/3" SONY DSP Super HAD High-Resolution CCD
- 550TV Lines Horizontal Resolution
- Min. Illumination : 0.1Lux
- Vandal Proof Dome Housing
- IP-66 Weatherproof Type
- Auto White Balance

Option

- Dual Voltage (AC 24V / DC 12V)
- Varifocal Lens : 4.0~9.0mm
- Board Lens : 3.6mm



1/3 SONY DSP Super HAD CCD



COLOR



DAY & NIGHT



VANDAL PROOF



VERI-FOCAL LENS



AUTO-IRIS





IP-66



DC 12V

- DIMENSION -



- 3 AXIS GIMBAL BRACKET -



- Camera Rotation : 360°
- Tilt Rotation : 100°
- Pan Rotation : 270°

- WALL MOUNT BRACKET -



MBR-SVCBR

- SPECIFICATION -

SVC-3242HQ		
Signal Format	NTSC	PAL
Horizontal Resolution	550TV Lines	
Image Sensor	1/3" SONY DSP Super HAD High-Resolution CCD	
Scanning System	525 lines interlaced	625 lines interlaced
Synchronization	Internal	
Video Output	Standard composite 1Vp-p composite video into 75Ω	
Min. Illumination	0.1Lux (B/W)	
Signal to Noise Ratio	45dB or more (AGC Off)	
Gamma	0.45	
AGC	On	
Input Voltage	DC 12V (±10%), 2.0W	
Housing Material	Vandal Proof Dome	
Operating Temperature	-10°C to +55°C	
Operating Humidity	Under 85% Non-condensing	
Lens	Varifocal Lens 2.8~11.0mm DC VF / F1.4 Board Lens 3.6mm	
Dimension	138(Φ) x 94.8(H)mm	
Weight	Approx. 690g	
Option	3-AXIS Bracket, AC 24V / DC 12V (Dual Voltage)	