

# VANDAL PROOF DOME CAMERA

## SVC-3242QF

### 3-AXIS, VANDAL PROOF DOME CAMERA



#### - FEATURES -



- 1/3" SONY DSP Super HAD High-Resolution CCD
- 550TV Lines
- True Day&Night  
: Filter Switching Mechanism ICR Lens Built-in
- Min. Illumination : 0.01Lux (B/W)
- Auto White Balance
- Vandal Proof Dome Housing
- IP-66 Weatherproof Type

#### Option

- Dual Voltage (AC 24V / DC 12V)
- Varifocal Lens : 2.8~11.0mm (ICR)



#### - DIMENSION -



#### - 3 AXIS GIMBAL BRACKET -



- Camera Rotation : 360°
- Tilt Rotation : 100°
- Pan Rotation : 270°

#### - WALL MOUNT BRACKET -



MBR-SVCBR

#### - SPECIFICATION -

SVC-3242QF		
Signal Format	NTSC	PAL
Horizontal Resolution	550TV Lines	
Image Sensor	1/3" SONY DSP Super HAD High-Resolution CCD	
Scanning System	525 lines interlaced	625 lines interlaced
Synchronization	Internal	
Video Output	Standard composite 1Vp-p composite video into 75Ω	
Min. Illumination	0.01Lux (B/W)	
Signal to Noise Ratio	45dB or more (AGC Off)	
Gamma	0.45	
AGC	On	
Input Voltage	DC 12V (±10%), 2.4W	
Housing Material	Vandal Proof Dome / IP-66	
Operating Temperature	-10°C to +55°C	
Operating Humidity	Under 85% Non-condensing	
Lens Option	Varifocal Lens 2.8~11.0mm (ICR)	
Dimension	138(Φ) x 94.8(H)mm	
Weight	Approx. 690g	
Option	3-AXIS Bracket, AC 24V / DC 12V (Dual Voltage)	