

IR LED CAMERA

TDE-221HF

21PCS IR LED VANDAL PROOF DOME CAMERA



- FEATURES -


- 1/3" SONY DSP Super HAD High-Resolution CCD
- 480TV Lines, B/W 600TV Lines
- 21pcs IR LED for night vision
- True Day & Night : Filter Switching Mechanism Built-in
- Visibility Range : 15~20m
- DC Varifocal Lens : 2.8~11.0mm/F1.4



1/3 SONY DSP
SUPER HAD CCD



COLOR



FILTER SWITCHING
MECHANISM




2.8~11.0mm
VARI-FOCAL LENS



21 pcs IR LED





DAY & NIGHT



DC 12V

- DIMENSION -



- SPECIFICATIONS -

TDE-221HF		
Signal Format	NTSC	PAL
Horizontal Resolution	Color : 480TV Lines, B/W : 600TV Lines	
Image Sensor	1/3" SONY DSP Super HAD High-Resolution CCD	
Scanning System	525 lines interlaced	625 lines interlaced
Synchronization	Internal	
Video Output	Standard composite 1Vp-p composite video into 75Ω	
True Day & Night	Filter Switching Mechanism Built-in	
Min. Illumination	Day : 3Lux, Night : 0.00Lux (IR LED On)	
Signal to Noise Ratio	45dB or more (AGC Off)	
Gamma	0.45	
AGC	On	
Input Voltage	DC12V (±10%)	
Power Consumption	Normal : 180mA, Max : 320mA	
Operating Temperature	-10°C to +55°C	
Storage Temperature	-20°C to +70°C	
Operating Humidity	Under 90% Non-condensing	
Storage Humidity	Under 90% Non-condensing	
Lens	Varifocal Lens 2.8~11.0mm/F1.4	
Dimension	140(Φ) x 96(H)mm	
Weight	Approx. 420g	