

# TDE-224H, TDE-224

## 24PCS IR LED COLOR DOME CAMERA



### IP66



#### - FEATURES -

- TDE-224H : 1/3" SONY High-Resolution Super HAD CCD  
TDE-224 : 1/3" SONY Super HAD CCD
- TDE-224H : 480TV Lines Horizontal Resolution  
TDE-224 : 380TV Lines Horizontal Resolution
- 24pcs IR LED (Day & Night)
- Visibility Range : 15~20m
- Board Lens : 3.6mm/F2.0
- IP 66



1/3 SONY DSP SUPER HAD CCD



COLOR



3.6mm BOARD LENS



24pcs IR LED



DAY & NIGHT



AUTO-IRIS





IP 66



DC 12V

#### - DIMENSION -



PANNING UPTO 360°



TILTING 10°~90°

#### - SPECIFICATIONS -

TDE-224H / TDE-224		
Signal Format	NTSC	PAL
Horizontal Resolution	TDE-224H : 480TV Lines, TDE-224 : 380TV Lines	
Image Sensor	TDE-224H : 1/3" SONY High-Resolution Super HAD CCD TDE-224 : 1/3" SONY Super HAD CCD	
Scanning System	525 lines Interlaced	625 lines Interlaced
Synchronization	Internal	
Video Output	CVBS : 1.0Vp-p / 75	
Min. Illumination	Day : 0.3Lux, Night : 0.00Lux (LED On)	
Signal to Noise Ratio	45dB or more (AGC Off)	
AGC	ON	
Housing Material	Metal	
Input Voltage	DC 12V (±10%)	
Power Consumption	LED Off : Max. 2.4W, LED On : Max. 4.8W	
Operating Temperature	-10°C to +55°C	
Operating Humidity	Under 85% Non-condensing	
Lens Option	Board Lens 6.0 / 8.0mm	
Dimension	93(Φ) x 80(H)mm	
Weight	Approx. 600g	