

TDE-236HVF**36PCS IR LED COLOR DOME CAMERA****IP66****- FEATURES -**

- 1/3" SONY DSP Super HAD CCD
- 480TV Lines Horizontal Resolution
- 36pcs IR LED (Day & Night)
- IR LED Off : 3Lux (Color), IR LED On : 0.000Lux
- Visibility Range : 15~20m
- Varifocal Lens : 2.8~11.0mm
- IP 66
- Adjustable Lens without opening case

1/3 SONY DSP
SUPER HAD CCD

COLOR

2.8~11.0mm
VARI-FOCAL LENS

36pcs IR LED





DAY & NIGHT



AUTO-IRIS

ELECTRONIC
SHUTTER

DC 12V

- DIMENSION -

PANNING UPTO 360°



TILTING 10°~90°

- SPECIFICATIONS -

TDE-236HVF		
Signal Format	NTSC	PAL
Horizontal Resolution	480 TV Lines	
Image Sensor	1/3" SONY DSP Super HAD CCD	
Scanning System	525 lines Interlaced	625 lines Interlaced
Synchronization	Internal	
Video Output	CVBS : 1.0Vp-p / 75	
Min. Illumination	Color : 3Lux, B/W : 0.002Lux (LED On)	
Electronic shutter	1/60 ~ 1/100,000 sec	1/50 ~ 1/100,000 sec
Signal to Noise Ratio	45dB (AGC Off)	
Gamma	0.45	
AGC	On	
DIP Switch Control	AI/EE Mode, AGC On/Off, Flickerless On/Off Backlight compensation On/Off	
Input Voltage	DC 12V (±10%)	
Power Consumption	LED Off : Max. 2.4W, LED On : Max. 6.5W	
Operating Temperature	-10°C to +55°C	
Storage Temperature	-20°C to +70°C	
Operating Humidity	Under 90% Non-condensing	
Storage Humidity	Under 90% Non-condensing	
Dimension	120(Φ) x 96(H)mm	
Weight	Approx. 800g	