

TDE-V224QS

24PCS IR LED DNR DOME CAMERA



IP67





- FEATURES -

- 1/3" SONY DSP Super HAD High-Resolution CCD
- 550TV Lines Horizontal Resolution
- Excellent Low Light Sensitivity of 0.3Lux/F1.2, 0Lux (LED On) (50 IRE, AGC High, DNR High) 0.002Lux (Sens-up x128)
- 24pcs IR LED for nigh vision
- Auto Day & Night On
- DNR : Digital Noise Reduction
- Board Lens 3.6mm
- Visibility Range : 15~20M
- IP-67 Weatherproof Type



- DIMENSION -



PANNING UPTO 360°



TILTING 10°~90°

- SPECIFICATIONS -

TDE-V224QS		
Signal Format	NTSC	PAL
Horizontal Resolution	Color : 550TV Lines, B/W : 600TV Lines	
Image Sensor	1/3" SONY High-Resolution Super HAD CCD	
Effective Pixels	768(H) x 494(V)	752(H) x 582(V)
Scanning System	2:1 Interlace	
Synchronization	Internal	
Scanning Frequency	15.734 KHz(H), 59.94 Hz(V)	15.625 KHz(H), 50.00 Hz(V)
Video Output	CVBS : 1.0Vp-p/75Ω	
Min. Illumination	LED OFF : 0.3Lux(Color), 0.002Lux(Sens-up), LED ON : 0Lux	
Electronic Shutter	1/60 ~ 1/120,000 sec	1/50 ~ 1/120,000 sec
IRIS Control	MANUAL	
Signal to Noise Ratio	50dB (AGC Off, Weight On)	
Backlight Compensation	Auto	
White Balance	Auto	
Gain Control	Auto	
3D-DNR	On	
Day & Night	AUTO	
Sens-up	AUTO	
Lens	Board Lens : 3.6mm	
Input Voltage	DC 12V (±10%)	
Power Consumption	LED OFF : Max 2.0W, LED ON : Max. 4.8W	
Operating Temp / Hum	-10°C to +50°C / 30% to 90% RH	
Storage Temp / Hum	-20°C to +60°C / 20% to 100% RH	
Dimension	93(Φ) x 80(H)mm	
Weight	Approx. 380g	