

TDE-W218QF

550TVL/18 IR LED VANDAL DOME CAMERA



IP66





- FEATURES -

- 1/3" SONY High-Resolution Super HAD CCD
- 550TV Lines Horizontal Resolution
- Excellent Low Light Sensitivity of 0.3Lux/F1.2 (B/W : 0.01Lux)
- 18EA IR LED (Visibility Range : 10~15m)
- True Day & Night : Built-in Filter Switching Mechanism
- DC Varifocal ICR Lens f=2.8~11.0mm
- Built-in OSD controller
- IP66 Weatherproof type
- 3-Axis gimbal bracket
- Vandal proof dome housing
- Dual voltage : AC 24V / DC 12V (Option)



- DIMENSION -



- 3 AXIS GIMBAL BRACKET -



- Camera Rotation : 360°
- Tilt Rotation : 100°
- Pan Rotation : 270°

- WALL MOUNT BRACKET -



MBR-401WM

- SPECIFICATIONS -

TDE-W218QF		
Signal Format	NTSC	PAL
Horizontal Resolution	420TV Lines	
Image Sensor	1/3" SONY Super HAD CCD	
Effective Pixels	768(H) x 494(V)	752(H) x 582(V)
Scanning System	2:1 Interlace	
Synchronization	Internal	
Scanning Frequency	15.734 KHz(H), 59.94 Hz(V)	15.625 KHz(H), 50.00 Hz(V)
Video Output	CVBS : 1.0Vp-p/75Ω	
Min. Illumination	Color : 0.3Lux/F1.2, B/W : 0.01Lux/F1.2	
Electronic Shutter	1/60 ~ 1/100,000 sec	1/50 ~ 1/100,000 sec
IRIS Control	DC	
Signal to Noise Ratio	45dB or more (AGC Off)	
Backlight Compensation	ON / OFF	
White Balance	AUTO	
Gamma	Adjustable	
Flickerless	ON / OFF	
Lens	DC Varifocal ICR Lens f=2.8~11.0mm	
Input Voltage	DC 12V (±10%)	
Power Consumption	LED Off : Max. 2.0W / LED On : Max. 4.0W	
Operating Temp/Hum	Temperature : -10°C ~ +50°C / Humidity : 30% ~ 80% RH	
Storage Temp/Hum	Temperature : -20°C ~ +60°C / Humidity : 20% ~ 90% RH	
Dimension	115.0(Ø) x 112.0(H)mm	
Weight	Approx. 960g	