

TEC-254QS

IP67/54 IR LED DNR CAMERA



IP67



- FEATURES -



- 1/3" SONY DSP Super HAD High-Resolution CCD
- 550TV Lines Horizontal Resolution
- Excellent Low Light Sensitivity of 0.3Lux/F1.2, 0Lux (LED On) (50 IRE, AGC High, DNR High) 0.002Lux (Sens-up x128)
- 54pcs IR LED for nigh vision
- Auto Day & Night On
- DNR : Digital Noise Reduction
- Board Lens 6.0mm
- Visibility Range : 30~40m
- IP67 Weatherproof Type
- All weatherproof anodized aluminum housing and sunshield

Option

- Audio



- DIMENSION -



- SPECIFICATIONS -

TEC-254QS		
Signal Format	NTSC	PAL
Horizontal Resolution	Color : 550TV Lines, B/W : 600TV Lines	
Image Sensor	1/3" SONY High-Resolution Super HAD CCD	
Effective Pixels	768(H) x 494(V)	752(H) x 582(V)
Scanning System	2:1 Interlace	
Synchronization	Internal	
Scanning Frequency	15.734 KHz(H), 59.94 Hz(V)	15.625 KHz(H), 50.00 Hz(V)
Video Output	CVBS : 1.0Vp-p/75Ω	
Min. Illumination	LED OFF : 0.3Lux(Color), 0.002Lux(Sens-up), LED ON : 0Lux	
Electronic Shutter	1/60 ~ 1/120,000 sec	1/50 ~ 1/120,000 sec
IRIS Control	MANUAL	
Signal to Noise Ratio	50dB (AGC Off, Weight On)	
Backlight Compensation	Auto	
White Balance	Auto	
Gain Control	Auto	
3D-DNR	On	
Day & Night	AUTO	
Sens-up	AUTO	
Lens	Board Lens : 6.0mm	
Input Voltage	DC 12V (±10%)	
Power Consumption	LED OFF : Max 1.0W, LED ON : Max. 6.4W	
Operating Temp / Hum	-10°C to +50°C / 30% to 90% RH	
Storage Temp / Hum	-20°C to +60°C / 20% to 100% RH	
Dimension	85(W) x 85(H) x 95.5(D)mm	
Weight	Approx. 450g	
Option	Audio	