

IR LED DOME CAMERA

TDE-224Q

24 IR LED DOME CAMERA



Body Color : Black / White

- FEATURES -

- 1/3" SONY High-Resolution Super HAD CCD
- 550TV Lines Horizontal Resolution
- 24pcs IR LED for night vision
- Visibility Range : 10~15m
- Auto White Balance
- Φ100 Dome size
- Board Lens : 3.6mm
- Vandal Proof Glass

Option

- Board Lens : 6.0mm



1/3 SONY
SUPER HAD CCD



COLOR



3.6mm
BOARD LENS



24pcs IR LED



DAY & NIGHT





AUTO-IRIS



DC 12V

- DIMENSION -



- SPECIFICATIONS -

TDE-224Q		
Signal Format	NTSC	PAL
Horizontal Resolution	550TV Lines	
Image Sensor	1/3" SONY High-Resolution Super HAD CCD	
Effective Pixels	768(H) x 494(V)	752(H) x 582(V)
Scanning System	2:1 Interlace	
Synchronization	Internal	
Scanning Frequency	15.734 Khz(H), 59.94 Hz(V)	15.625 Khz(H), 50.00 Hz(V)
Video Output	CVBS : 1.0Vp-p/75Ω	
Min. Illumination	0.3Lux/F1.2	
Electronic shutter	1/60 ~ 1/100,000 sec	1/50 ~ 1/100,000 sec
IRIS Control	DC / MANUAL	
Signal to Noise Ratio	45dB or more (AGC Off)	
Backlight Compensation	ON / OFF	
White Balance	AUTO	
Gain Control	AUTO	
Gamma	0.45	
Flickerless	ON / OFF	
Input Voltage	DC 12V (±10%)	
Power Consumption	LED Off : Max. 2.4W, LED On : Max. 4.8W	
Operating Temp/Hum	-10°C to +55°C / Under 85% Non-condensing	
Storage Temp/Hum	-20°C to +70°C / Under 90% Non-condensing	
Dimension	118(Φ) x 73(H)mm	
Weight	Approx. 420g	