

IR LED DOME CAMERA

TDE-224SL

24 IR LED DOME CAMERA



Body Color : Black / White

- FEATURES -

- 1/3" SONY DSP Super HAD CCD
- 380TV Lines Horizontal Resolution
- 24pcs IR LED for night vision
- Visibility Range : 10~15m
- Auto White Balance
- Φ100 Dome size
- Board Lens : 3.6mm
- Vandal Proof Glass

Option

- Board Lens : 6.0mm



1/3 SONY DSP
Super HAD CCD



COLOR



3.6mm
BOARD LENS



24pcs IR LED



DAY & NIGHT





AUTO-IRIS



DC 12V

- DIMENSION -



- SPECIFICATIONS -

TDE-224SL		
Signal Format	NTSC	PAL
Horizontal Resolution	380TV Lines	
Image Sensor	1/3" SONY Super HAD CCD	
Scanning System	525 lines interlaced	625 lines interlaced
Synchronization	Internal	
Video Output	CVBS : 1.0Vp-p/75Ω	
Min. Illumination	0.3Lux/F1.2 (LED Off), 0Lux (LED On)	
Electronic Shutter	1/60 ~ 1/100,000 sec	1/50 ~ 1/100,000 sec
Signal to Noise Ratio	45dB or more (AGC Off)	
Gamma	0.45	
AGC	On	
LED Qty	24	
Input Voltage	DC 12V (±10%)	
Power Consumption	LED On : Max. 4.8W, LED Off : Max. 2.4W	
Operating Temperature	-10°C to +55°C	
Storage Temperature	-20°C to +70°C	
Operating Humidity	Under 90% non-condensing	
Storage Humidity	Under 90% non-condensing	
Lens	Fixed Lens 3.6mm	
Dimension	118(Φ) x 73(H)mm	
Weight	Approx. 420g	
Option	Fixed Lens 6.0mm	