

TDE-V224QS2

24PCS IR LED DNR DOME CAMERA



IP67



- FEATURES -


- 1/3" SONY High-Resolution Super HAD CCD II
- Color 580TV Lines, B/W 700TV Lines
- Excellent Low Light Sensitivity of 0.15Lux/F1.5 (LED Off)
- Sens-up x2 ~ x256 (Color : 0.0006Lux, B/W : 0.000004Lux)
- 24pcs IR-LED for night vision (0 Lux)
- DNR : Digital Noise Reduction
- HLC : High Light Compensation
- DIS : Digital Image Stabilizer
- IP 67 System
- Visibility Range : 15~20M



1/3 SONY DSP Super HAD CCD



Color



Day & Night



DNR DIGITAL NOISE REDUCTION



Sens-up 0.000004Lux




54pcs IR LED



BOARD LENS




IP 67




DC 12V

- DIMENSION -



80



PANNING UPTO 360°



TILTING 10°~90°

- SPECIFICATIONS -

TDE-V224QS2		
Signal Format	NTSC	PAL
Horizontal Resolution	Color : 580TV Lines, B/W : 700TV Lines	
Image Sensor	1/3" SONY High-Resolution Super HAD CCD II	
Effective Pixels	768(H) x 494(V)	752(H) x 582(V)
Scanning System	2:1 Interlace	
Synchronization	Internal	
Scanning Frequency	15.734 KHz(H), 59.94 Hz(V)	15.625 KHz(H), 50.00 Hz(V)
Video Output	CVBS : 1.0Vp-p/75Ω	
Min. Illumination	LED OFF : 0.15Lux(Color), 0.0006Lux(Sens-up), LED ON : 0Lux LED OFF : 0.001Lux(B/W), 0.000004Lux(Sens-up), LED ON : 0Lux	
Electronic Shutter	1/60 ~ 1/120,000 sec	1/50 ~ 1/120,000 sec
IRIS Control	MANUAL	
Signal to Noise Ratio	52dB (AGC Off, Weight On)	
Backlight Compensation	Auto	
White Balance	Auto	
Gain Control	Auto	
DNR	Digital Noise Reduction	
Day & Night	Auto	
Sens-up	Auto	
DIS	Digital Image Stabilizer	
Lens	Board Lens : 3.6mm	
Input Voltage	DC 12V (±10%)	
Power Consumption	LED OFF : Max 2.0W, LED ON : Max. 4.8W	
Operating Temp / Hum	-10°C to +50°C / 30% to 90% RH	
Storage Temp / Hum	-20°C to +60°C / 20% to 100% RH	
Dimension	93(Φ) x 80(H)mm	
Weight	Approx. 380g	