

SPEED DOME CAMERA

TDX-2026S

INDOOR SPEED DOME CAMERA



- FEATURES -

Fast & Silent Motion

- No accumulative error with preset function
- Shortest path by vector drive technology
- High accuracy with micro-stepping control technology
- Smooth motion at high zoom magnification mode
- Lightning speed (MAX. 360°/sec) & Smooth manual speed (MIN. 0.05°/sec)
- Lowest noise & Lowest vibration
- Endless 360°/sec Pan Rotation

Superior Zoom Camera

- x312 Zoom Control (Optical x26, Digital x12)
- Day & Night (IR Cut Filter)

Powerful Functions

- Independent preset characteristic setup (AE, WB and etc.)
- 128 Preset positions with alphanumeric labels
- 4 Pattern, 8 Swing and 8 Group functions
- 8 Privacy Zones (Spherical Coordinates)
- Auto flip, Auto parking, Power-up action
- On-screen display On/Off
- Built-in Sensor In/Out function (4 In / 2 Out)
- Small Size / Vandal-Proof (Dome Cover : PC / Housing & Accessories : AL)
- Network Function (Optional)



- MECHANISM SPECIFICATIONS -

TDX-20***	
Range	Pan : 360°(Endless) / Tilt : 95°
Pan/Tilt Speed	Preset : 360°/sec
	Manual : 0.05°~360°/sec (Zoom Proportional)
	Swing : 1°~180°/sec
Preset	128 Presets with Labels
Patterns	4 Patterns (Approx. 5 Minutes for each pattern)
Swing	8 Swings
Group	8 Groups (MAX. 20 Entries for Each Pattern)
Other Functions	Auto Flip, Auto Parking, Power-up Action & etc
Communication	RS-485
Protocol	Pelco-D, Pelco-P Selectable
Privacy Zone	8 Zones
Sensor In / Out	Built-in 4 Input / 2 Output
OSD	English On / Off
Pan / Heater	Built-In
Power	AC Type : AC 24V / 0.6A
	DC Type : DC 12V / 1.0A (Option)
Dimension	Dome : 149(Φ) / 5.9"(H)
	Housing : 160(Φ) x 212(H)mm / 6.3"(Φ) x 8.3"(H)
Weight	Approx. 2Kg / 4.4Lbs
Operating Temp	0°C ~ 40°C / 32°F ~ 104°F

- REMOTE CONTROLLER -



WTX-1200A (PTZ CONTROLLER)

* Preset, Group, Tour, Swing, Pattern, Monitor Setting, Menu, Speed Control, Display, Interface convert.

- CAMERA SPECIFICATIONS -

TDX-2026S		
Signal Format	NTSC	PAL
Image Sensor	1/4" SONY EX-View CCD	
Effective Pixel	380K Pixels	440K Pixels
Horizontal Resolution	480TV Lines	
Signal to Noise Ratio	More than 50dB	
Zoom	x26 Optical Zoom and x12 Digital Zoom	
Focal Length	F1.6~3.8, f=2.5~65mm	
Min. Illuminance	Color : 0.3Lux, B/W : 0.003Lux	
Day & Night	Auto / Day / Night (ICR)	
Focus	Auto / Manual / Semi-Auto	
AE mode	Auto / Iris / Shutter / Manual Brightness	
White Balance	Auto / Manual (Red, Blue Gain Adjustable)	
BLC	On / Off	
Flickerless	On / Off	

- BRACKET & SUN SHEILD -



Wall Mount Type
(MBR-201W)



Ceiling Mount Bracket
(MBR-201C)



In-Ceiling Mount Type
(MBR-201CF)