

TEC-236L

IP67/35 IR LED COLOR CAMERA



IP67



- FEATURES -

- 1/3" SONY Super HAD CCD
- 420TV Lines Horizontal Resolution
- Excellent Low Light Sensitivity of 0.3Lux/F1.2
- 35pcs IR-LED for night vision (Day & Night)
- Visibility Range : 20~25m
- Board Lens : 6.0mm
- IP67
- All weatherproof anodized aluminum housing and sunshield

Option

- Audio



1/3 SONY SUPER HAD CCD



COLOR



DAY & NIGHT



BOARD LENS



35pcs IR LED



IP 67



DC 12V

- BRACKET -



- SPECIFICATIONS -

TEC-236L		
Signal Format	NTSC	PAL
Horizontal Resolution	420TV Lines	
Image Sensor	1/3" SONY Super HAD CCD	
Effective Pixels	510(H) x 492(V)	500(H) x 582(V)
Scanning System	2:1 Interlace	
Synchronization	Internal	
Scanning Frequency	15.734 KHz(H), 59.94 Hz(V)	15.625 KHz(H), 50.00 Hz(V)
Video Output	CVBS : 1.0Vp-p/75Ω	
Min. Illumination	LED Off : 0.3Lux/F1.2, LED On : 0Lux/F1.2	
Electronic shutter	1/60 ~ 1/100,000 sec	1/50 ~ 1/100,000 sec
IRIS Control	MANUAL	
Signal to Noise Ratio	48dB or more (AGC Off)	
White Balance	AUTO	
Gain Control	AUTO	
Gamma	0.45	
Lens	Board Lens f=6.0mm (Option : 3.6mm / 8.0mm / 12.0mm)	
LED Qty	35 pcs	
Input Voltage	DC 12V (±10%)	
Power Consumption	LED On : Max. 4.8W / LED Off : Max. 1.0W	
Operating Temperature	-10°C to +60°C	
Storage Temperature	-20°C to +70°C	
Dimension	76(W) x 76(H) x 85(D)mm	
Weight	Approx. 380g	
Option	Audio	