

WTX-1200C

DVR/PTZ CONTROLLER



- FEATURES -

- Can control the DVR functions (Display, Sequence, Spot, Emergency, Enent, Setup, Play/Panse, etc.) and also PTZ Cameras
- Controls from 1 ~ 255 cameras.
- Multiple protocol supported in each channel
- RS-485 / RS-422 communication (Tx : 3 port, Trx : 1 port)
- Programmable user preferences. (Preset, Tour, Pattern, etc.)
- Built-in 3-Axis proportional joystick
- Easy upload programmed data via serial communication.
- USB mouse function
- Built-in 2 lines character LCD.
- User password support
- Programmable transmission speed for each ID. (2.4~57.6kbps)
- Operate with 9V battery
- DVR interface

- SPECIFICATIONS -

WTX-1200C	
Keyboard	Interface : RS-485 (Tx 3 port, Trx 1 port)
Communication	Pan/Tilt operating distance : 4700ft (1029m) on 24 AWG wire Multiple Protocol Support (Baud rate selectable) Terminal Block (8p connector)
Keyboard Keypad	Rubber button Numeric keypad and camera function key
Joystick	Proportional 3-Axis, variable speed with zoom
Input Voltage	12VDC or 9V battery (battery mode)
Power Consumption	Max.140mA
LCD Display	2 lines character LCD
Operating Temperature	0 to 45C
Humidity	10%~70% RH
Certification	280(W) x 92(H) x 174(D)mm
Dimensions	700g
Weight	Key Board, Adapter, 9V Battery, USB Cable, Manual, Terminal Block (8Pin)