

# VANDAL PROOF DOME CAMERA

## WVC-427QS2/DV55

### 600TVL/D-WDR VANDAL DOME CAMERA



# IP66



#### - FEATURES -

- 1/3" SONY High-Resolution Super HAD II CCD
- 600TV Lines Horizontal Resolution
- Excellent Low Light Sensitivity of 0.3Lux/F1.2
- Day & Night
- Digital WDR : Digital Wide Dynamic Range
- DNR : Digital Noise Reduction
- HLC : High Light Compensation
- Blemish Compensation : 64 Points
- Lens Shading
- Parking Line
- RS-485 Communication (Pelco-D/P)
- Built-in OSD Controller
- DC Varifocal Lens f=5.0~50.0mm / F1.4
- 3-Axis Gimbal Bracket
- IP66 Weatherproof Type / Vandal Proof Dome Housing

**Option :** Audio, Dual Voltage (DC 12V / AC 24V)  
Wall Mount Bracket (MBR-401WM)



1/3 SONY  
SUPER HAD II CCD



DAY & NIGHT



DIGITAL  
WDR  
DIGITAL WIDE  
DYNAMIC RANGE



DNR  
DIGITAL NOISE  
REDUCTION



HLC  
HIGH-LIGHT  
COMPENSATION



AUTO IRIS



5.0-50.0mm  
VARIFOCAL LENS



IP 66



VANDAL PROOF





3-AXIS GIMBAL



DC 12V

#### - DIMENSION -



#### - 3 AXIS / DUAL VOLTAGE / LOOP-OUT / OSD -



- Camera Rotation : 360°
- Tilt Rotation : 100°
- Pan Rotation : 270°



- Dual Voltage AC24V/DC12V
- Video Loop out / Cable
- OSD Controller

#### - WALL MOUNT BRACKET -



- MBR-401WM
- Concealed Bracket
- (Cable Built in the Bracket)

#### - SPECIFICATIONS -

WVC-427QS2/DV55		
Signal Format	NTSC	PAL
Horizontal Resolution	600TV Lines	
Image Sensor	1/3" SONY High-Resolution Super HAD II CCD	
Total Pixels	811(H) x 508(V)	795(H) x 596(V)
Effective Pixels	768(H) x 494(V)	752(H) x 582(V)
Scanning System	2:1 Interlace	
Synchronization	Internal	
Scanning Frequency	15.734 KHz(H), 59.94 Hz(V)	15.625 KHz(H), 50.00 Hz(V)
Video Output	CVBS : 1.0Vp-p/75Ω	
Min. Illumination	0.3Lux/F1.2	
Electronic Shutter	1/60 ~ 1/100,000 sec	1/50 ~ 1/100,000 sec
Iris Control	DC	
Signal to Noise Ratio	52dB (AGC Off, Weight : On)	
Backlight Compensation	BLC / HLC / OFF	
White Balance	ATW1 (2,300°K ~ 9,500°K) / ATW2 (2,000°K ~ 11,000°K) / MANUAL	
Gain Control	LOW / HIGH / OFF	
DNR	ON / OFF (Level Adjustable)	
Day & Night	AUTO / COLOR / BW / EXT	
Digital WDR	ON / OFF	
Motion Detection	ON / OFF (4 Zone, 48x15)	
Privacy	ON / OFF (8 Zone)	
Horizontal Mirror	ON / OFF	
Communication	Protocol : Pelco D/P, Cam ID 255, 2400 ~ 57600	
Lens Shading	ON / OFF	
Parking Line	User Setting (LT, LB, RT, RB, F, N, T)	
OSD	Built-in (English, Chinese)	
Lens	DC Varifocal Lens f=5.0-50.0mm / F1.4	
Input Voltage	DC 12V (±10%)	
Power Consumption	Max. 2.0W	
Operating Temp/Hum	Temperature : -10°C ~ +50°C / Humidity : 30% ~ 80% RH	
Storage Temp/Hum	Temperature : -10°C ~ +50°C / Humidity : 30% ~ 80% RH	
Dimension	155(Ø) x 112(H)mm	
Weight	Approx. 950g	