

IR LED CAMERA

TEC-C212L

12 IR LED CAMERA



- FEATURES -

- 1/3" SONY Super HAD CCD
- 420TV Lines Horizontal Resolution
- Excellent Low Light Sensitivity of 0.3Lux/F1.2
- LED On : 0Lux
- 12pcs IR LED for night vision
- Day & Night
- Auto White Balance
- Auto Gain control
- Visibility Range : 12~15mm
- Fixed Lens : 2.9mm

Option

- Audio



1/3 SONY
SUPER HAD CCD



COLOR



DAY & NIGHT



2.9mm
BOARD LENS






12pcs IR LED



DC 12V

- DIMENSION -



- I-TYPE -



TEC-C212LI

- SPECIFICATIONS -

TEC-C212L		
Signal Format	NTSC	PAL
Horizontal Resolution	420 TV Lines	
Image Sensor	1/3" SONY Super HAD CCD	
Effective Pixels	510(H) x 492(V)	500(H) x 582(V)
Scanning System	2:1 Interlace	
Synchronization	Internal	
Scanning Frequency	15.734 KHz(H), 59.94 Hz(V)	15.625 KHz(H), 50.00 Hz(V)
Video Output	CVBS : 1.0Vp-p / 75Ω	
Min. Illumination	Color : 0.3 Lux, B/W : 0.01Lux, LED On : 0Lux	
Electronic Shutter	1/60 ~ 1/100,000 sec	1/50 ~ 1/100,000 sec
IRIS Control	MANUAL	
Signal to Noise Ratio	48 dB (AGC Off)	
White Balance	AUTO	
Gain Control	AUTO	
Day & Night	IR LED On	
Gamma	0.45	
Lens	Fixed Lens : 2.9mm	
LED Qty	12 pcs	
Input Voltage	DC 12V (±10%)	
Power Consumption	Max. 3.2W	
Operating Temp / Hum	Temperature : -10°C to +50°C / Humidity : 30% to 80% RH	
Storage Temp / Hum	Temperature : -20°C to +60°C / Humidity : 20% to 90% RH	
Dimension	82(W) x 48(H) x 55.7(D)mm	
Weight	Approx. 170g (W/O Bracket)	
Option	I-Type, Audio	