

DXC-312

DVR BUILT-IN CAMERA



- FEATURES -


CAMERA

- 1/3" SONY Super HAD CCD
- 420TV Lines horizontal resolution
- Excellent low light sensitivity of 0.3Lux/F1.2 (B/W : 0.01Lux/F1.2)
- Auto Day & Night
- Auto white balance
- Built-in OSD controller
- DC controlled varifocal lens
- Strong compatibility with various lens type


DVR

- Display resolution - NTSC : 352x240 / PAL : 352x288
- Recording resolution - NTSC : 352x240 / PAL : 352x288
- Only play mode resolution : 704x480
- SD memory card type : 2GB / 4GB / 8GB / 16GB / 32GB
- Pre/Post-recording 20sec
- Motion detection recording
- Schedule recording
- Alarm input / output : 1ea / 1ea
- Remote controller


- FRONT -



- REAR -



- GUI -



MAIN MENU



PLAYER PROGRAM

- RECORDING TIME -

1GB SD CARD	30f/s	15f/s	7f/s	1f/s
HIGH	2H	4H	8H	16H
NORMAL	2.5H	5H	10H	20H
LOW	3H	6H	12H	24H

- SPECIFICATIONS -

DXC-312		
DVR	Compression Format	H.264
	Operation System	RTOS
	Only Play Mode Resolution	704x480
	Display Resolution	NTSC : 352x240 / PAL : 352x288
	Recording Resolution	NTSC : 352x240 / PAL : 352x288
	Recording Frame Rate	NTSC : 30 frames/sec / PAL : 25 frames/sec
	Recording Mode	Manual / Sensor / Motion Detection
	Storage	SD Card Memory
	Sensor Input	1pin terminal block
CAMERA	Signal Format	NTSC / PAL
	Horizontal Resolution	420TV Lines
	Image Sensor	1/3" SONY Super HAD CCD
	Scanning System	2:1 Interlace
	Synchronization	Internal
	Video Output	CVBS : 1.0Vp-p/75Ω
	Min. Illumination	Color : 0.3Lux/F1.2, B/W : 0.01Lux/F1.2
	Electronic Shutter	NTSC : FLK / FIXED / MANUAL / AUTO (1/60 ~ 1/100,000 sec) PAL : FLK / FIXED / MANUAL / AUTO (1/50 ~ 1/100,000 sec)
	Signal to Noise Ratio	50dB (AGC Off)
	Backlight Compensation	ON / OFF
	White Balance	ATW / AWC / FIXED / MANUAL
	Gain Control	ON / OFF
	Day & Night	COLOR / BW / AUTO
	Gamma	Adjustable
	Flickerless	ON / OFF
	Motion Detection	ON / OFF
	Privacy	ON / OFF
	Mirror	ON / OFF
	Sharpness	ON / OFF (Level adjustable)
	OSD	Built-in (Chinese, English, Japanese, Korean)
Input Voltage	DC 12V (±10%)	
Power Consumption	Max. 4.8W	
Operating Temp/Hum	Temperature : -10° to +50°C / Humidity : 20% to 80% RH	
Storage Temp/Hum	Temperature : -20° to +60°C / Humidity : 20% to 90% RH	
Dimension	63.0(W) x 64.5(H) x 121.5(D)mm	
Weight	Approx. 360g	

* Specifications are subject to change without notice.