

TBC-21 Series

Ø21 BULLET CAMERA



IP66



- FEATURES -

- 1/3" SONY Super HAD CCD
- 420TV Lines Horizontal Resolution
- Excellent Low Light Sensitivity of 0.3Lux/F1.2
- Software Day & Night
- Auto White Balance
- Auto Gain control
- IP66 Weatherproof Type

Lens option

- Board Lens : 3.6 / 6.0 / 8.0 / 12.0mm
- Conical Pinhole Lens : 3.3 / 4.3mm
- Semi Pinhole Lens : 3.7mm



- OPTIONAL MODEL -



TBC-21B
Board Lens Type



TBC-21W
Weatherproof Type



TBC-21CP
Conical Pinhole Lens Type




TBC-21SP
Semi Pinhole Lens Type

- DIMENSION -


Board Lens Type




Weatherproof Type




Conical Pinhole Lens Type



Semi Pinhole Lens Type



Mount Bracket



- SPECIFICATIONS -

TBC-21 Series		
Signal Format	NTSC	PAL
Horizontal Resolution	420TV Lines	
Image Sensor	1/3" SONY Super HAD CCD	
Effective Pixels	510(H) x 492(V)	500(H) x 582(V)
Scanning System	2:1 Interlace	
Synchronization	Internal	
Scanning Frequency	15.734 KHz(H), 59.94 Hz(V)	15.625 KHz(H), 50.00 Hz(V)
Video Output	CVBS : 1.0Vp-p/75Ω	
Min. Illumination	0.3 Lux/F1.2	
Electronic Shutter	1/60 ~ 1/100,000 sec	1/50 ~ 1/100,000 sec
IRIS Control	MANUAL	
Signal to Noise Ratio	48dB (AGC Off)	
White Balance	AUTO	
Gain Control	AUTO	
Day & Night	Software Day & Night	
Gamma	0.45	
Lens	Board Lens : 3.6 / 6.0 / 8.0 / 12.0mm Conical Pinhole Lens : 3.3 / 4.3mm Semi Pinhole Lens : 3.6mm	
Input Voltage	DC 12V (±10%)	
Power Consumption	Max. 1.8W	
Operating Temperature	-10°C ~ +60°C	
Storage Temperature	-20°C ~ +70°C	
Operating Humidity	Under 85% Non-condensing	
Storage Humidity	Under 90% Non-condensing	
Dimension	21(Ø)	
Weight	Approx. 80g	