

TDE-124QL

TDN/24 IR LED DOME CMOS CAMERA



IP67



- FEATURES -


- 1/3" CMOS Image Sensor
- 540TV Lines Horizontal Resolution
- Excellent Low Light Sensitivity of 0.1Lux/F1.2(LED On : 0Lux)
- 24ea IR LED (Visibility Range : 17~23m)
- True Day & Night (ICR)
- Auto White Balance
- Auto Gain Control
- Plastic Case Material
- Board Lens f=3.6mm
- IP67 Weatherproof Type

Option


- TDE-124QLB : Black Color Case
- TDE-124QLW : White Color Case



- DIMENSION -



- ROTATION -



Panning up to 360°



Tilting 10° ~ 90°

- SPECIFICATIONS -

TDE-124QL	
Video IO Select	NTSC / PAL
Horizontal Resolution	540TV Lines
Image Sensor	1/3" CMOS Image Sensor
Total Pixels	762(H) x 504(V)
Scanning System	Interlace
Synchronization	Internal
Scanning Frequency	15.734 KHz(H), 59.944 Hz(V)
Video Output	CVBS : 1.0Vp_p / 75Ω
Min. Illumination	0.1Lux / F1.2
Iris Control	AUTO
Signal to Noise Ratio	More than 45dB
White Balance	AUTO
Gain Control	AUTO
Day & Night	AUTO (ICR)
Lens	Board Lens f=3.6mm
LED Quantity	24 EA
Material	Plastic case
Input Voltage	DC 12V (±10%)
Power Consumption	LED Off : Max. 0.9W / LED On : 4.4W
Operating Temp.	-10°C ~ +50°C
Storage Humidity	30% ~ 90% RH
Dimension	94(Ø) x 84(H)mm
Weight	Approx. 120g