

MCL-520SE

52INCH TFT LCD MONITOR



- FEATURES -

- Metal Case
- Wide Screen Display (HD Resolution)
- Two Looping composite Input & Output
- One Looping S-Video Input & Output
- Two Audio Input and Output
- VGA and DVI Input
- VGA Input
- 3-D Digital Comb Filter with De-interlace for High Quality Video
- Picture In Picture (PIP), Picture By Picture (PBP)
- Remote Control Included
- Internal Speakers
- Desk Stand Included
- External Speaker (Optional)
- 100/240 VAC, 60/50Hz Autoranging Internal Power Supply

- FRONT VIEW -



- SIDE VIEW -



- BACK VIEW -



- INPUT / OUTPUT TERMINALS -



- CONTROL BUTTONS -



- WALL MOUNT BRACKET -



MCL-4250W

- Material is steel which is very strong and semi permanent.
- With horizontal control handle, we can install monitors horizontally.
- VESA : 468x450mm(Max)
- Maximum weight of LCD : 80Kg
- For 21 to 52 inch
- Tilt(V) : -15 to +15 degree
- COLOR : Black or Silver
- Size : 800 x 500 x 62 mm
- Net : 4.3kg

- SPECIFICATIONS -

MCL-520SE		
GENERAL	Model	52" inch LCD monitor
	Native Resolution	1920(H) x 1080(V) x RGB
	Panel Aspect Ratio	16:9
	Pixel Pitch	600um x 600um
	Brightness	700cd/m ²
	Contrast Ratio	2000:1
	Panel Life	50,000 hours
	Viewing Angle(H/V)	178°/178°
	Response Time	8ms
	Display Colors	16.7M
	PIP	Selectable, sizable, swappable, moveable
	POP	Swappable
	Video Formats	480i, 480p, 576i, 576p, 720p, 1080i
	Front Panel Controls	Power, Source/enter, menu/exit, up, down, volume minus, volume plus
ELECTRICAL	Indicators	LED(power on/off)
	Input Voltage	AC 100~240VAC, 50/60Hz
INPUT INTERFACES	Power Consumption	380W
	Video	DVI Input, D-Sub Input, Component Input, S-Video Input/Output, BNC Input x 2, BNC Output x 2
	Audio	2 audio L/R, RCA jack, 1 stereo mini jack, looping
	Horizontal Frequency	31KHz to 69KHz
	Vertical Frequency	56Hz to 85Hz
PHYSICAL	Sync Format	NTSC/PAL
	Dimensions(without stand-WxHxD)	1232.8 x 756.6 x 113.5mm
	Unit Weight	41kg
	Shipping Weight	47kg